



PERMASTRUCT® FRP Care Guide

PermaStruct® recommend you use the following methods to clean and care for your PermaStruct® FRP products.

Please Note: With any cleaning product used, test it on a small inconspicuous area first and always follow the manufacturers instructions. DO NOT use bleach, as it will lighten the product.

Frequency	PermaStruct® recommend to clean weekly or on a regular schedule to avoid any build up of soil or dirt. This can be done with a pressure washer.
General Dirt and Debris	Use warm soapy water or an Alkaline Detergent Solution and scrub with a medium bristle brush to clean dirt and debris from grooves / contours. Finish off by using a pressure washer to remove any more stubborn stains.
Oil / Grease / Food / Drink	If something is spilt on PermaStruct® FRP, remove and mop as soon as possible. If required, spray with a hose / pressure washer or use warm soapy water and a medium bristle brush.
Ice and Snow	Simply use a broom to remove any snow. If there is any remaining frozen precipitation / ice that requires melting, use Rock Salts or Calcium Chloride.
Rust Stains and Engrained Dirt	Cleaning products containing Oxalic or Phosphoric Acid can be used. Apply Oxalic Acid neatly with a brush directly to the effected area. Leave for 10 to 15 minutes and then wash off with a Pressure Washer. DO NOT use bleach as this will lighten the product.
Mould and Mildew	Mould and mildew can grow on surface residue that has been left. To remove, mop as soon as possible and if required use warm soapy water with a medium bristle brush or hose with a pressure washer.
Marking for Cutting	Always use non-permanent markers such as baby powder, dust-off marking chalk or plum line whenever possible.

10/11/2022