

## PermaTimber® QuickBoard™ – Warranty & Installation Guide v1.2

Read this guide in full before installation. Correct installation of PermaTimber® QuickBoard™ ensures long-lasting performance and enjoyment. This product is designed for ceilings, eaves, interior patios, and alfresco linings, not for locations exposed to direct or reflective sunlight.

### IMPORTANT WARRANTY CONDITIONS

Failure to follow the guidelines below will void your warranty.

- Pre-Installation Inspection

PermaTimber® QuickBoard™ panels are inspected for quality before packaging and shipping. Stock delivered to stores is inspected upon arrival and should be free from damage. All products collected from a retailer should be thoroughly inspected at the time of pickup. Any damages discovered at that point should be addressed directly with the retailer.

- Product Suitability

This product is not suitable for direct sunlight or areas exposed to strong reflective sunlight and cannot be installed under polycarbonate or clear roofing. Panels may vary slightly in colour, and such variation is not covered under warranty. 2.7m and 4.8m panels should not be mixed in the same installation area.

- Batch Consistency

For large projects, ensure all materials are ordered together to maintain batch consistency. If multiple batches are on site, contact your distributor before installation.

- Thermal Clearance Requirements

A sufficient clearance is required when installed under a steel roof to allow for ventilation. PermaTimber® QuickBoard™ must not be fixed directly to roof metal purlins or any building components that could become hot, such as metal roofing or areas exposed to significant sunlight. A thermal barrier must be installed.

- Installation Guidelines

Panels must be installed in accordance with the official installation guide, which can be downloaded by scanning the QR code. Ensure adequate expansion and contraction gaps are allowed around the panels and lay out panels before fixing to achieve a uniform texture and appearance. All fixing points near electrical sources must be installed safely by a licensed electrician. Clips required for installation are included in the box.

